ALMASat Alma Mater Satellite



ALMASat Microsatellite Platform for Small Scientific Experiments in Orbit



Giulio Pezzi IZ4FVW - AB2VY

RF Engineer

Team collaborator of :

II School of Aerospace Engineering
University of Bologna
Via Fontanelle 40, Forlì

ALma MAter Satellite

ALMASat Alma Mater Satellite



Summary:

- ALMASat Laboratory
- The Microsatellite Program in Forlì
- The Forlì Ground Station
- ALMAtraker
- S-Band subsystem tests
- ALMASat-1 Microsatellite
- Conclusions

ALMASat Alma Mater Satellite

University of Bologna, Forlì
Aerospace Campus

Main research and educational buildings

Microsatellite Laboratory

ALMASat Alma Mater Satellite



Available facilities

- A VHF/UHF/S amateur ground station;
- Digital electronics prototyping (PC, power supplies, oscilloscope, function generator @ 15MHz, JTAG emulator for Atmel® AVR microcontrollers;
- RF prototyping (at VHF, UHF and S bands);
- A test bench for the experimental validation of micropropulsion systems, a 15l, 200 bar, Nitrogen tank, pressure regulators, micro-valves, digital and analogue manometers and data acquisition systems;
- A glove box (100x100x150 cm) for solar panels assembly and integration;
- A Hardware-In-the-Loop (HIL) simulation test bench;
- A momentum/reaction wheels test platform
- A rotating platform for calibration of attitude sensors (accuracy of 1/100 of a degree)

ALMASat Alma Mater Satellite

The microsatellite program in Forlì

- Design, assembly and set-up of an **amateur radio station** ⇒ **fully operational**
- Design and assembly of a **Multi-mission satellite platform,** modular configuration
- Launch of the first microsatellite prototype,
  Alma Mater Satellite - ALMASat (in the second half of 2008)



The Alma Mater Ground Station (AMGS)

ALMASat Alma Mater Satellite



- **2003:**
  - ***Design e setup of the ground station***
    - External mast, rotors, UHF and VHF antennas
    - Hardware assembly for station control and signal RX
    - Commercial software
- **2005:**
  - ***S-band downlink channel implementation***
    - Installation of an integrated receiving system
    - Hardware updates
    - New S/W for station control simultaneous RX in multiple bands
- **2006:**
  - ***Design and implementation of a new electronic board for rotor control***
    - Software updates

AMGS in 2003 (1/2)



- C.O.T.S.
- Communicati
  UHF/VHF ba
- Automated tr
- 3 manageme



Kantronics

ve Computer:
Telemetry

AMGS in 2003 (2/2)



AMGS in 2005

ALMASat Alma Mater Satellite



Antenna
Rotor System

SHF

VHF
Preamplifier

Icom
CT-17

RS-232

Modem Ka
KPC 9

Parallel Port

Connected

Master Computer:
Radios and Rotor Control

Slave Computer:
UHF/VHF & S-Band
Telemetry

External instrumentation upgrade in 2005

ALMASat Alma Mater Satellite

Technical characteristics:

- Polarization: RHCP
- Diameter: 70 cm
- λ: 0.245
- f/D: 0.35
- Mast diameter: ø 40 - 60 mm
- Input frequency: 2407-2409 MHz
- Output frequency: 437-439 MHz
- Gain: 36 dB
- Noise figure: typ. 0.9 dB
- Operational voltages: 11 - 15 V



- **Down-converter and mast support assembly**
- **Positioning at 50 cm from vertical mast to avoid misalignments**

S/W upgrades in 2006

S/W upgrades for the new rotor control system

- **Ready for Voice and Data S-band reception of AO-51 and other satellite**

AlmaTracker

High precision (~0.01°) tracking system for satellite ground stations

AlmaTracker

Prototype of control board for AlmaTracker



ALMASat Alma Mater Satellite

S-Band satellite subsystem

- **Modulator CX72302** Dual Fractional-N Frequency Synthesizer
- **2407 Mhz RF Power Amplifier**
- **Quadrifilar Antenna**



Test , developement and other issue by:

Giulio Pezzi iz4fvw@iz4fvw.net **and**

Ing. Gianpaolo Candini
gianpaolo.candini@unibo.it

Direct Digital Modulation (DDM)







DDM

FSK (Frequency shift keying)

0 → f_1

1 → f_2



PLL programmabl
run time

ALMASat Alma Mater Satellite

S-Band satellite subsystems



FFSK 2.4 GHz Modulator,
Control interface and PA

ALMASat Alma Mater Satellite

S-Band satellite subsystem test



FFSK 2.4 GHz
Modulator

ALMASat Alma Mater Satellite

S-Band satellite subsystem test

Data Clock Generator

ALMASat Alma Mater Satellite

S-Band Transmission test

KU 2425-LEO2

S-band Power



KU 2425-LEO2, Amplifier

Center frequency: 2400 MHz

Operation bandwidth: 50 MHz

Gain flatness: +/- 1dB

Nominal input power: 0 dBm +/- 0,5 dB

Input overdrive: +10 dBm

RF Input interface: SMA connector female

Input VSWR less than 1,6:1

Output power: 35 dBm, +/- 1 dB over the operating bandwidth

Output power stability: +/- 1 dB (ambient temperature range 10 - 30 °C)

Gain compression: at 35 dBm output power over the whole bandwidth not less than 3 dB

Output is protected with an isolator

Harmonic levels shall be not more than -30 dBc

Output interface: SMA connector female

Output VSWR less than 1,6 :1

Noise figure: 12 dB

Operating voltage: 12 ... 13,8 V (intern linear stabilized)

SSPA efficiency: approx. value will be around 22%.

ALMASat Alma Mater Satellite

S-Band Transmission test



Test of modulator “on air” with no preamplifier before the power amplifier

S-Band satellite subsystem test

Voltmeter, connected

to the power test point

on the output of the final amplifier, showing a value relative to 0.5 watt RF

ALMASat Alma Mater Satellite

S-Band satellite subsystem test

Current absorbed without the input preamplifier

ALMASat Alma Mater Satellite

S-Band satellite subsystem test

ZX60 Mini-Circuits input

ALMASat Alma Mater Satellite

S-Band satellite subsystem test



System test with attenuator before the spectrum analyzer

ALMASat Alma Mater Satellite

S-Band Transmission test



Output signal with attenuators

ALMASat Alma Mater Satellite

S-Band satellite subsystem test

Voltage reference for an output power of 4.5 W RF (@2380 Mhz)

S-Band satellite subsystem test

Voltage and current absorbed by the system at the max output power (4.5 W RF @2380 Mhz)

S-band quadrifilar antenna



ALMASat Alma Mater Satellite

ALMASat-1 Microsatellite

ALMASat is a three-axis stabilized platform



ALMASat-1 Subsystems Layout

- Final layout of S/C subsystems:



6 UHF-VHF Radio RX-TX

5 Modem + Telemetry board

4 Battery packs

3 Micropropulsion System

2 ADCS

1 Power board + S-band TX



ALMASat-1 Electronics and RF block diagram



ALMASat-1: Launch Options (1/2)

- **ALMASat-1** can be launched by a converted SS-19 intercontinental missile from the **Baikonour Cosmodrome** (Kazahstan)
- The **DNEPR** program was started by a Russian-Ukrainian collaboration in 1999 focused on the civilian conversion of former nuclear weapons
- **University of Bologna**

ALMASat-1: Launch Options (2/2)

- **ALMASat-1** can also be launched by the new small European launcher **VEGA** from **Kourou** (French Guyana)
- The **VEGA** missile has its maiden flight scheduled for 2008, fully compatible with our schedule
- **University of Bologna** has undertaken



ALMASat Alma Mater Satellite

ALMASat Alma Mater Satellite



The End ...

73 from ..

Giulio Pezzi

IZ4FVW - AB2VY

RF Engineer

II School of Aerospace Engineering

University of Bologna

Via Fontanelle 40, Forlì (Italy)